

OVNI 345

Standard SPECIFICATION and INVENTORY

(Customised versions subject to quotation)

2 LAYOUTS : 2-CABIN (standard) or
3-CABIN version (optional)

I. DECK FITTINGS

All external woodwork in Burmese teak
Non-slip coating on all surfaces
Anodised stemhead fittings with two bow rollers for anchor
Painted aluminium toerail
Self-draining chain locker, fixing point for anchor chain
Electric windlass 1.000 W
S/s Swedish pulpit w. bi-coloured approved lights
S/s stern pushpits with horseshoe buoy bracket
S/s central stern helmsman's seat
Sheathed double lifelines on s/s stanchions on each side
2 spring cleats midships 260 mm
2 bow mooring cleats 330 mm
2 stern mooring cleats 330 mm
1 cleat 260 mm and stern roller on stbd side
Anodised aluminium chain plates
2 deck hatches 500 x 500 and 450 x 320
4 hatches on coach roof coaming 325 x 185
3 fixed hull portholes of tinted plexiglas 600 x 150 (4 in 3-cabin version)
2 tinted plexiglas side windows on coach roof coaming 2,550 x 250
1 mainsheet track
2 genoa sheet tracks
2 winch handles
2 44 ST genoa sheet winches
2 halyard winches on coach roof, 16 ST & 32 ST
2 genoa turning blocks
2 triple-sheave blocks for halyard led back to cockpit + centreboard lifting rope
1 triple-cam clutch to starboard
1 triple-cam halyard clutch led to cockpit stbd
1 single cam clutch on mast
2 stainless steel handrails on coach roof
Water and fuel fillers on deck and vents
Cold shower on stern
External engine ventilation on stern
Bathing platform with s/s ladder and teak steps
Roller on stern
Life raft storage in stern
1 radar arch/gantry aft for electronics/davits
Approved stern light on arch

II. RIGGING

Deck stepped mast with double spreaders
Mast head light, deck light
Genoa furling system
Stainless steel standing rigging
1 forestay
1 V-shaped backstay (double insulated backstay as an option)
2 upper shrouds
2 intermediate shrouds
4 lower shrouds
1 kicking strap with tackle
Mainsheet tackle
1 mainsail halyard
1 genoa halyard
1 spinnaker halyard
1 boom topping lift + 1 spiboom topping lift
3 reefing lines
1 16 ST reefing winch
2 genoa sheets
Mainsheet, mainsail and spinnaker halyards and 2 for centreboard are led back to cockpit, the topping lift stays at the mast.

III. SAILS

Mainsail with 3 rows of reefs, bag and slats
Furling genoa

IV. COCKPIT

Large self-draining cockpit
Aluminium trap for fitting the emergency tiller
Slatted teak cockpit seats
Teak grating
Steering wheel, diameter 800 mm, with compass and compass box
Coaming lockers
Aluminium rudderstock
Gas bottle locker
Large lockable cockpit locker to starboard with

- sandow
- storage box for washboards
- manual bilge pump

1 opening porthole 347 x 171

OVNI 345 — SPECIFICATION — PAGE 2

V. COMPANIONWAY

Smoked Plexiglas sliding hatch
Smoked Plexiglas washboards in two-part with ventilation and s/s lock
Solid teak frame
2 teak handrails, 330 mm
Companionway steps in solid wood with non-slip strips
Removable companionway steps for easy access to the engine
Engine instrument panel

VI. NAVIGATION AREA

Chart table, 690 x 625 (according to chosen model)
Locker under chart table Book shelf and storage space
Main switch panel with 13 functions, 12 V and 220 V sockets and fuel gauge
Ventilation through 325 x 185 deck hatch
Wiring ducts for connecting electronic equipment to mast and hull bottom
1 neon light
Slatted navigator's seat with storage below
Chart storage desk
Instrument panel and flow meter (available as option)
1 spotlight
1 handrail on coaming 330

VII. SALOON

L-shaped settee
Cushions, 10 cm thick
Storage unit
Laminated teak striped floor
Ventilation through 450 x 320 deck hatch
Light through plexiglas on coach roof coaming and fixed portholes
4 spotlights
Vinyl headlining, oak trimmed
Painted aluminium mast support
Bookcase to starboard
Saloon table on centreboard case with 1 or 2 leaves (in 3-cabin version) of 1360 x 550 mm
2 teak handrails, 840, on coaming
Curtains

VIII. GALLEY

L-shaped arrangement
White laminate worktop (Surrell optional)
2 rectangular s/s sinks built into the worktop
Pressurized hot and cold water
Storage cupboard under sink
Gimballed s/s two-burner stove with oven with s/s protection rail

45 litre refrigerator (air cooled)
3 storage cupboards above worktop, one with dish section
Ventilation through 325 x 185 deck hatch on coaming
1 neon light
1 handrail on coaming 330
Seawater foot pump
1 spotlight
Locker behind sink with bottle rack
Light through smoked plexiglas on coach roof
1 220 V socket
Wood hull lining, vinyl head lining

IX. FORWARD CABIN

Double berth
Upholstered mattress, 10 cm thick
Storage compartments under berth
Hanging locker, storage locker
Ventilation and light through 500 x 500 deck hatch
Cabin door (lockable) to saloon with restraining hook.
1 spotlight & 2 adjustable reading lamps
Laminated teak striped floor

SINGLE AFT CABIN VERSION

X. AFT CABIN

Double berth, 200 x 160 x 100
Upholstered mattress, 10 cm thick
Storage and hanging lockers
Light through hull porthole 600 x 150 with curtain
Ventilation through opening cockpit porthole 347 x 171
Ventilation through opening porthole on coaming 325 x 185
Cabin door (lockable) to saloon with restraining hook.
Inspection hatch to engine forming small locker
1 spotlight & 2 adjustable reading lamps
Laminated teak striped floor
Vinyl headlining
Circuit breaker under berth

XI. AFT TOILET/SHOWER

Head located to stbd of the companionway
Cabin door (lockable) to saloon
White laminate bulkheads
Toilet (manual pump)
Washbasin + pressurized tap/shower
1 electric shower pump
Porthole on coach roof coaming 325 x 185

OVNI 345 — SPECIFICATION — PAGE 3

Cabinet with storage space
Teak shower grating
1 neon light & 1 spotlight
Laminate worktop with locker behind washbasin
Locker on bulkhead
Inspection hatch to engine forming small locker
Holding tank 80 L in one aft cabin version – smaller in two aft cabins version

TWIN AFT CABINS VERSION (Optional)

XII. AFT CABINS

Double berth, 195 x 140 x 100
Upholstered mattress, 12 cm thick
Storage and hanging lockers
Light through hull portholes 600 x 150
1 ventilation through opening cockpit porthole 347 x 171
1 ventilation through opening porthole on coaming 325 x 185
Cabin door (lockable) to saloon w. hook.
Inspection hatch to engine
1 spotlight & 2 adjustable reading lamps
Laminated teak striped floor
Vinyl headlining
Storage space & circuit breaker under berth

XIII. FORWARD TOILET/SHOWER

Head located forward of the mast
Cabin door (lockable) to saloon
White laminate bulkheads
Toilet (manual pump)
Washbasin + pressurized tap/shower
1 electric shower pump
Light through porthole on coach roof coaming 325 x 185
Cabinet with storage space
Teak shower grating
1 neon light & 1 spotlight
Laminate worktop w. locker behind washbasin
Locker on bulkhead
Holding tank 50 L

XIV. ENGINE UNIT

Volvo 30 hp diesel engine
Soundproofed and ventilated engine compartment
Insulated two-pole engine
Ventilation: 1 air inlet and 1 air outlet
3 12 V -70 Ah batteries (1 engine + 2 auxilliary)
Battery charger and load distributor
22 l water heater; boiler: supply 220 V and via heat exchanger (engine)

Electric bilge pump
Engine instrument panel in companionway; single-lever control
Two-blade cupro-aluminium propeller, shaft with anode

XV. SPECIFIC FEATURES

Architect: JOUBERT - NIVELT
Design : P. ROSEO
Construction: our boats are built from 5083 H 111 aluminium and welded in an Argon/ Helium atmosphere.
Interior woodwork in oak; vinyl headlining.
Lead ballast encapsulated in waterproof resin

CENTREBOARD & RUDDER MECHANISM

Tackle for centreboard lifting and lowering
Rudder hydraulic cylinder & bursting disk.
Aluminium dual function pump (centreboard & rudder) in aft storage compartment

GENERAL SPECIFICATIONS

Length overall	11.48 m
Hull length	10.93 m
Length at waterline	9.10 m
Maximum beam	3.60 m
Draught centreboard down	2.10 m
Draught centreboard up	0.58 m
Light displacement	7,000 kg
Ballast weight	2,900 kg
Water tanks	228 l
Fuel tank	191 l
Gross tonnage	12.62 t
C.E. Approval Class	A

SAIL FEATURES

Sail area on the wind	67 m ²
Mainsail	27.5 m ²
Genoa	39.5 m ²
Stormsail (optional)	6 m ²
Spinnaker (optional)	80 m ²
I(mast) / J / P / E (m)	13.20 / 3.90 / 11.75 / 3.78

HEADROOM

Companionway	1.92 m
Galley	1.90 m
Saloon aft	1.92 m
Saloon forward	1.88 m
Cabin aft	1.90 m
Cabin forward	1.83 m
Toilet aft	1.90 m
Toilet forward	1.85 m

OPTIONS

Please contact us for a list of optional equipment.

This specification is non contractual and can be amended without notice.