

RHEA 650

STANDARD SPECIFICATION

Construction

Hull and deck reinforced polyester laminate

Hull bottom: balsa sandwich

Wooden bulwark Rail

Deck Facilities

Walkaround Deck Layout

Self-draining chain locker

Stem head anchor roller

2 fairleads forward and aft

2 mooring cleats forward and aft

7 handrails on deckhouse and wheelhouse

Stainless bow pulpit

2 seater bench on foredeck

2 dorade cabin ventilators

Engine facilities

Diesel engine, prop shaft drive with protected propeller

Soundproofed engine compartment

200 litre fuel tank

Engine start and control panel in wheelhouse

Diesel gauge

Propeller access hatch (option)

Cockpit & deck

2.45 m x 2.45 m x 0.72 m Self-draining cockpit

Transom door

1 Stern locker (access to hydraulic steering ram)

2 side lockers/storage

1 engine casing

Cockpit (cont'd)

1 emergency tiller

2 rod holders

1 rod rack in locker

Wheelhouse

11 safety-glass windows

1 side sliding door

1 sliding aft door

1 electric windscreen wiper

1 helm

Engine Control

Pilot seat

Instrument console

Locker

3 handrails

Bench with locker

Cabin

2 berths

Lockers below berths

Various storage spaces

Electrical equipment

1 12 volt, 95 amp battery

Electrical distribution panel

Cabin, head and wheelhouse lighting

Bilge pump

Dimensions:

LOA: 6.50m

Beam: 2.70m

Draught: 0.60m

Weight: 1,800 kg

Engine: 60 to 130hp diesel

Fuel tank: 200 litres.