

RHEA 750 OPEN

STANDARD SPECIFICATION

Construction

Hull and deck: reinforced polyester laminate

Hull bottom: balsa sandwich

Deck: PVC foam sandwich

Wooden bulwark rail

Deck facilities

Walkaround deck layout

Self-draining chain locker

Stem-head anchor roller

2 fairleads forward and aft

2 mooring cleats forward and aft

4 handrails on coachroof

1 opening deck hatch

Stainless bow pulpit

2 opening cabin portholes

Engine Facilities

Diesel engine, prop shaft with protected propeller

Soundproofed engine compartment

210-litre diesel tank

Engine start and control panel on console

Diesel gauge

Cockpit & deck

3 m x 2.5 m x 0.67 m self draining cockpit

2.4 m x 2.3.m foredeck for sunbathing

Transom door

4 watertight deck lockers

1 deck locker that converts to fish well

1 removable U-shaped banquette with 3 lockers

1 stainless mast

4 seat banquette

1 engine casing

1 emergency tiller

2 rod holders

Steering Position

Adjustable seats for helmsman and co-pilot

Engine controls & panel

Instrument console

Stainless framed glass windshield

Step

Steering compass

Cabin

1 fitted galley

40 litre refrigerator

2 ring burner

Sink with pressurized water

55 litre water tank

Storage

Head with sea toilet

Large double bunk

2 facing banquettes with seat squabs and backs

Open side lockers

Lockers under bunk and banquettes

Electrical equipment

1 12 volt, 105 Amp battery

Electrical distribution panel

Cabin, head and galley lighting

Navigation lights

Bilge

Dimensions

LOA: 7.50m

Beam: 2.80m

Draft: 0.70m

Weight: 2,500 kg

Engine: 200 to 315hp diesel

Fuel tank: 210 litres

Transmission: shaft drive

Hydraulic steering

CE Category B