

RHEA 750

STANDARD SPECIFICATION

Construction

Hull and deck reinforced polyester laminate
Wooden bulwark rail

Deck facilities

Walkaround deck layout

Self draining chain locker
Stem-head anchor roller
2 fairleads forward and aft
2 mooring cleats forward and aft
7 handrails on coachroof and wheelhouse
Stainless bow pulpit
2 seater bench on foredeck

Engine Facilities

Diesel engine, prop shaft drive with protected propeller
Soundproofed engine compartment
300-litre fuel tank
Engine start & control panel in wheelhouse
Diesel gauge
Propellor access hatch (option)

Cockpit & deck

2.90 m x 2.50 m x 0.75 m self draining cockpit
Transom door
1 stern locker (access to hydraulic steering ram)
2 side cockpit locker/seats
1 engine casing
1 emergency tiller
2 rod holders
1 aft cockpit locker (converts to fish tank - option)

Wheelhouse

9 safety-glass windows
1 sliding side door
1 sliding aft door

1 electric windscreen wiper
1 hydraulic steering wheel
Instrument console
Steering compass
Access to bilge locker
2 seats with storage beneath
Foldaway table

Galley

Sink with pumped water
Single gas burner
55 litre fresh water tank
3 handrails

Cabin

2 berths
Lockers below berths
1 marine toilet between berths
1 opening porthole

Electrical equipment

1 x 12 volt, 105 Amp battery
Electrical distribution panel
Cabin and wheelhouse lighting
Navigation lights
Bilge pump

Dimensions

LOA: 7.48m
Beam: 2.80m
Draught: 0.70m
Weight: 2,500kg
Engine: 150 to 230 hp diesel
Fuel tank: 300 litres
Transmission: Shaft drive
Hydraulic steering
CE Category B